

# FMVCJS3 SERIES

3.3 Vdc VCXO

## J - LEAD PLASTIC SMD



- Low Profile
- 3.3 Vdc Supply Voltage
- HCMOS/TTL Compatible
- Tape & Reel




### SPECIFICATIONS

09 - Issue 2 - 021209


Parameter	Specification
Frequency Range	1.8 - 200 MHz
Overall Frequency Tolerance	±25 ppm to ±100 ppm (Inclusive of Operating Temp., Supply Voltage, & Load.)
Operating Temperature Range	0 to +70°C Std.
Storage Temperature	-40 to +125°C
Supply Voltage (Vdd)	+3.3 Vdc (±0.5 Vdc)
Supply Current (Icc)	30 mA max. @ 2.0 to 23.9 MHz 50 mA max. @ 24.0 to 55.0 MHz 75 mA max. @ 56.0 to 200.0 MHz
Symmetry (Duty Cycle)	40/60% Std., 45/55% Available (See Spec. Option S).
Output "0" Level (VoL)	0.4 Vdc max. (TTL) 0.5 Vdc max. (HCMOS)
Output "1" Level (VoH)	2.4 Vdc min. (TTL) 4.5 Vdc min. (HCMOS)
Rise and Fall Time	10 ns max. < 5 ns typical
Linearity	±20% max. Std., ±10% Available (See Spec. Option L)
Output Load	10 TTL / 15 pF HCMOS < 40.0 MHz 15 pF HCMOS
Pullability	±100 to ±150 ppm typical. (Select a min. and max. pullability from part number.) Voltage Control Pin 1 Nom. 2.5 Vdc, Range 0.5 to 4.5 Vdc
Control Voltage (Vc)	Nominal 2.5 Vdc, Range 0.5-4.5 Vdc, Positive Transfer
Aging @ 25°C	±3 ppm max first year

All specifications subject to change without notice.

### J-LEAD PLASTIC SMD



### Recommended Land Pattern



### STANDARD MARKING



XX.XXM FREQUENCY IN MHz  
XXXXXXX Part Number  
ESD/Pin 1 Symbol, FMI, Date Code

### PIN FUNCTION TABLE

Pin	Function
1	Control Voltage (Vc)
7	Case Ground
8	Output
14	Supply Voltage (Vdd)

Standard Specifications for product indicated in color

Dimensions:  $\frac{\text{Inches}}{\text{(mm)}}$

### PART DESCRIPTION SYSTEM

FMVCJS3 50 C E A S / L - XX.XXXXXXM - CM

