


FMVC33 SERIES

3.3 Vdc VCXO

14 PIN DIP




- 3.3 Vdc Supply Voltage
- HCMOS/TTL Compatible
- Low Current Consumption
- High Frequency



SPECIFICATIONS

09 - Issue 2 - 021209

Parameter	Specification
Frequency Range	20.0 kHz to 200 MHz (Std.)
Overall Frequency Tolerance	±20 ppm to ±100 ppm (Inclusive of Operating Temp., Supply Voltage, & Load.)
Operating Temperature Range	0 to +70°C Std.
Storage Temperature	-55 to +125°C
Supply Voltage (Vdd)	+3.3 Vdc (±0.3 Vdc)
Supply Current (Icc)	15 mA max. @ 20.0 kHz to 23.9 MHz 30 mA max. @ 24.0 to 60.0 MHz 75 mA max. @ 61.0 to 160.0 MHz 90 mA max. @ 161.0 to 200.0 MHz
Symmetry (Duty Cycle)	40/60% Std., 45/55% Available. (See Spec. Option S)
Output "0" Level (VOL)	0.4 Vdc max. (TTL) 0.4 Vdc max. (HCMOS)
Output "1" Level (VOH)	2.4 Vdc min. (TTL) 2.7 Vdc min. (HCMOS)
Rise and Fall Time	10 ns max. < 5 ns typical
Linearity	±20% max. Std., ±10% Available (See Spec. Option L)
Output Load	10 TTL / 15 pF HCMOS < 40.0 MHz 15 pF HCMOS
Pullability	±50 to ±125 ppm Available. (Select a min. and max. pullability from part number.) Voltage Control Pin 1 Nom. 1.65 Vdc, Range 0.0 to 3.3 Vdc
Jitter (typical)	< 10 pico seconds, one sigma
Phase Noise (typical)	10 Hz -75dBc/Hz 100 Hz -110dBc/Hz 1kHz -125dBc/Hz 10kHz -130dBc/Hz 100kHz -140dBc/Hz
Control Voltage (Vc)	Nominal 1.65 Vdc, Range 0.0-3.3 Vdc, Positive Transfer
Aging @ 25°C	±3 ppm max first year



PIN FUNCTION TABLE

Pin	Function
1	Control Voltage (Vc)
7	Case Ground
8	Output
14	Supply Voltage (Vdd)

All specifications subject to change without notice.

STANDARD MARKING

XX.XXM
XXXXXXXX
• FMI YYWW

XX.XXM FREQUENCY in MHz
XXXXXXXX Part Number
ESD/Pin 1 Symbol, FMI, Date Code

Dimensions: $\frac{\text{Inches}}{\text{(mm)}}$

Standard Specifications for product indicated in **color**

PART DESCRIPTION SYSTEM

